

Replacement pump KTP/SPZ 1000 230 V, cable length 5 m



Article information

Item no.: 28351 GTIN: 4026092038420 Price group: 90

Description

Replacement pump with macerator for wastewater with sewage

Variant Pump control:	Control unit
General characteristics Standard: Type of wastewater:	EN 12050-1 with sewage
Dimensions Net weight: Gross weight: Packaging dimension: Packaging dimension: Packaging dimension:	10,29 kg 10,62 kg length width height
Pumping device Pump: Connection type: Operating voltage: Mains frequency: Protection class: Insulation class: Cos phi - power factor: Protection class (pump): Temperature monitoring: Max. temperature (permanent) of conveyed material:	SPZ 1000 coded plug 230 V 50 Hz I F 0,97 IP 68 (3m/48h) integrated 35 °C
material: Max. pumping height: Speed: Power P1: Power P2: Operating mode:	10 m 2800 U/min 1,2 kW 0,7 kW S3 - 50 %



Type of pump connection cable: Impeller type: Length of mains cable for pump: Rated current:

Control Operating voltage: Connection type: Type of fuse required (electrical protection): H07RN-F 3G 1.5 mm² Macerator 5 m 5,2 A

230 V coded plug Fuse protection through control unit 230 V