

## Comfort control unit 400V, Aqualift Duo, 2x2.5-4.0 A



### Article information

Item no.: 28757  
 GTIN: 4026092055021  
 Price group: 20

### Advantages

- Self-diagnosis system (SDS)
- Potential-free contact for faults/warnings
- Reminder for when maintenance is due

### Description

Comfort control unit for lifting stations or pumping stations. Suitable for 400 V double stations. Optional connection options for float switches, conductivity probes, and level probes on the terminal strip. User-friendly menu navigation on the multi-line display. Menu navigation in six languages. Simple selection of the system to be connected with preset, system-specific operating parameters. Display of current measured values. Simple adjustment of function-relevant parameters, with integrated operating hour counter. With self-diagnosis system (SDS) for monitoring pump, sensors and battery back-up. Improper installation or operating faults trigger an optical and acoustic alarm signal. Forwarding of a collective fault and alarm signal via optional potential-free contact or integrated serial interface for a GSM modem.

#### Variant

Series: ab 03/2010  
 Type of system: duo pump

#### General characteristics

Colour: grey  
 System type: Duo

#### Dimensions

Net weight: 3,17 kg  
 Gross weight: 3,83 kg  
 Packaging dimension: length  
 Packaging dimension: width  
 Packaging dimension: height

#### Control

Control unit: Comfort  
 Motor protection switch: yes  
 Protection class control unit: IP 54

Potential-free contact:	yes
GSM interface:	yes
USB interface:	no
Log book function:	yes
Multi-line display:	yes
Battery buffering:	yes
Self-diagnosis system (SDS):	yes
Rated current:	2,5 - 4 A