



Variofix upper section Kessel des cov, 304 SST, Lock&Lift, L15





Article information

Item no.: 48904

GTIN: 4026092028841

Price group: 10

Advantages

- Different covers selectable
- Including waterproofing membrane

Description

Used in combination with a drain body of the KESSEL modular system, the upper section is suitable for indoor point drainage.

Variant

System: 125 Seal: Lip seal

Waterproofing layer on the upper section: Enclosed sealing collar to be glued (bd) according to

DIN 18534

Water exposure class in accordance to DIN

18534-1 (up to and including):

W3-I

Dimensions

Vertical adjustment: 10 - 23 mm
Net weight: 1,55 kg
Gross weight: 1,77 kg
Diameter: 312 mm

Type of height adjustability: vertically adjustable upper section

Height: 120 mm
Packaging dimension: length
Packaging dimension: width
Packaging dimension: height

Coverage features

Type of cover: Design cover

Cover material: Stainless steel 14301



Colour of cover: silver

Frame material: Stainless steel 14301

Locking: Lock & Lift
Load class: L 15 (EN 1253-1)

Grating design: Kessel

Slip resistance class: R9 according to DIN 51130; C according to DIN

51097

Rim width: 132 mm Rim length: 132 mm

Upper section: adjustable in three dimensions

Shape of upper section: square Upper section material: ABS