


Upper section with slotted cover d: 218 mm, A/L15



Article information

Item no.: 67986
GTIN: 4026092085493
Price group: 10

Advantages

- Multiple combinations with suitable drain bodies

Description

The polymer upper section is suitable for LW 400 chamber systems and is equipped with a clamping ring and a hanger for sludge buckets. Continuously height-adjustable by 440 mm. If installed in roads, parking areas and comparable hard-surfaced traffic areas for trucks (Class D), the upper section must be underlaid on site with an approx. 15 cm thick reinforced supporting slab with at least 0.80 x 0.80 m made of B35 concrete. The exact design of the concrete slab must be calculated structurally according to the circumstances on site. A standard formwork and reinforcement drawing can be provided.

Variant

System: 200

Dimensions

Net weight: 4,4 kg

Gross weight: 4,9 kg

Diameter: 218 mm

Type of height adjustability: vertically adjustable upper section

Packaging dimension: length

Packaging dimension: width

Packaging dimension: height

Coverage features

Cover material: Polymer

Colour of cover: black

Load class: A 15 (EN 124) / L 15 (EN 1253-1)

| | |
|-------------------------|---------|
| Rim width: | 300 mm |
| Rim length: | 300 mm |
| Upper section material: | Polymer |