

## Grease separator EasyClean free NS 2, Standard, Ref. in., Insp. Win., SC



## **Article information**

Item no.: 93002.32 GTIN: 4026092063422 Price group: 60

## **Advantages**

- Direction of flow can be changed thanks to selfsealing interchangeable hubs (NS 2- NS 10)
- Can be retrofitted up to Auto Mix & Pump
- Low-maintenance operation

## Description

The separator for greasy wastewater is suitable for free-standing set-up in frostprotected rooms and comes without metallic components in the tank. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap and has a tapered base for fast and clean disposal. Two odour-tight covers with quick-release closures make easy access possible for cleaning and maintenance work. Manual disposal is carried out with the tank open. 20 year polyethylene warranty.

Variant	
Disposal variant:	Standard
Shredder-Mix-System:	no
Sludge bucket:	yes
Nominal size (NS):	2,00
SonicControl:	yes
Refill inlet in accordance with DIN 1988:	yes
Type of disposal:	manual with suction hose
Load-bearing capacity (DIN 19901):	F3
General characteristics Material: Installation situation: Delivery state:	PE free-standing installation Installation-ready (connection parts must be connected on site)
Dimensions Net weight: Gross weight: Set-up area, length: Set-up area, width:	98,5 kg 128,5 kg 1736 mm 674 mm



Set-up area, height:	1434 mm
Required access area, length:	1500 mm
Required access area, width:	674 mm
Required access area, height:	1434 mm
Packaging dimension:	length
Packaging dimension:	width
Packaging dimension:	height
Tank/drain body	
Distance pipe bottom outlet to tank bottom:	985 mm
Distance pipe bottom inlet to tank bottom:	1055 mm
Outlet nominal size (OD):	110 mm
Outlet nominal size (DN):	100 mm
Inlet nominal size (OD):	110 mm
Inlet nominal size (DN):	100 mm
Connection inlet/outlet sockets:	PE-HD pipes in accordance with DIN 19537, HT pipes
	in accordance with DIN 19560, PP or AS
	III accordance with div 19560, PP of AS
	III accordance with Din 19500, PP of AS
Coverage features	
Type of cover:	Cover
Type of cover: Cover material:	Cover Polymer
Type of cover: Cover material: Colour of cover:	Cover Polymer violet
Type of cover: Cover material: Colour of cover: Locking:	Cover Polymer violet Quick-release closure
Type of cover: Cover material: Colour of cover:	Cover Polymer violet
Type of cover: Cover material: Colour of cover: Locking: Tightness:	Cover Polymer violet Quick-release closure
Type of cover: Cover material: Colour of cover: Locking: Tightness: Wastewater contents	Cover Polymer violet Quick-release closure odour-tight
Type of cover: Cover material: Colour of cover: Locking: Tightness: Wastewater contents Separator contents:	Cover Polymer violet Quick-release closure odour-tight
Type of cover: Cover material: Colour of cover: Locking: Tightness: Wastewater contents Separator contents: Total volume:	Cover Polymer violet Quick-release closure odour-tight 400 l 600 l
Type of cover: Cover material: Colour of cover: Locking: Tightness: Wastewater contents Separator contents: Total volume: Contents of sludge trap:	Cover Polymer violet Quick-release closure odour-tight 400 l 600 l 200 l
Type of cover: Cover material: Colour of cover: Locking: Tightness: Wastewater contents Separator contents: Total volume:	Cover Polymer violet Quick-release closure odour-tight 400 l 600 l
Type of cover: Cover material: Colour of cover: Locking: Tightness: Wastewater contents Separator contents: Total volume: Contents of sludge trap: Storage quantity of grease:	Cover Polymer violet Quick-release closure odour-tight 400 l 600 l 200 l
Type of cover: Cover material: Colour of cover: Locking: Tightness: Wastewater contents Separator contents: Total volume: Contents of sludge trap:	Cover Polymer violet Quick-release closure odour-tight 400 l 600 l 200 l