

## Aqualift F XL, 450 L lift. stat. Duo, SPF 4500-S3, 2 shut-off valves



### Article information

Item no.: 11071  
 GTIN: 4026092057384  
 Price group: 50

### Advantages

- Different performance classes available
- Pressure sensor for reliable pneumatic level measurement
- Maximum operating reliability due to intelligent control unit (Duo)

### Description

The lifting station for faecal and faecal-free wastewater is equipped with one or two submersible pumps and a backflow preventer. The collection tank made of permanently resistant polymer (PE) offers universal connection options and has a screwed access cover.

#### Variant

|                           |                                     |
|---------------------------|-------------------------------------|
| Type of system:           | duo pump                            |
| Shut-off valve:           | 2 shut-off valves made of cast iron |
| Pressure pipe connection: | vertical                            |

#### General characteristics

|                         |                            |
|-------------------------|----------------------------|
| Colour:                 | black                      |
| Standard:               | EN 12050-1                 |
| Type of wastewater:     | with sewage                |
| Installation situation: | free-standing installation |
| System type:            | Duo                        |

#### Dimensions

|                      |          |
|----------------------|----------|
| Net weight:          | 220,6 kg |
| Gross weight:        | 240,6 kg |
| Packaging dimension: | length   |
| Packaging dimension: | width    |
| Packaging dimension: | height   |

#### Tank/drain body

|              |       |
|--------------|-------|
| Tank volume: | 450 l |
|--------------|-------|

#### Pumping device

|       |             |
|-------|-------------|
| Pump: | SPF 4500-S3 |
|-------|-------------|

|  |                     |
|--|---------------------|
| Number of pumps:                               | 2                   |
| Operating mode:                                | S3 - 50 %           |
| Type of fuse required (electrical protection): | 3 x C 25 A          |
| Impeller type:                                 | Multi-vane impeller |
| Free passage:                                  | 40 mm               |
| Length of mains cable for pump:                | 5 m                 |
| Control  |                     |
| Control unit:                                  | Comfort             |
| Level measurement instrument:                  | Immersion pipe      |
| Type of level measurement:                     | pneumatic           |
| Mains frequency:                               | 50 Hz               |
| Operating voltage:                             | 400 V               |
| Type of fuse required (electrical protection): | 3 x C 25 A          |