


Drain body The Universal DN 100, AISI304 grat., Backwater protect





Article information

Item no.: 27621 GTIN: 4026092007839 Price group: 10

Advantages

PΡ

- Flexible installation: vertically adjustable upper section rotatable
- Integrated backwater protection
- vertically adjustable

Description

The polymer drain body is equipped with a removable backwater valve with two backwater flaps, one hand-lockable emergency closure and a sludge bucket. The drain body also has two inlets DN 50 and one inlet DN 70 with blind plug. Material:

- Variant Contents of sludge trap: Emergency closure: Waterproof flange: Mechanical backwater flaps:
- General characteristics Colour: Standard: Nominal size (DN): Outer diameter (OD): Type of wastewater: Installation situation: Delivery state: Backwater protection: Odour trap:

yes yes Pre-assembled at the factory 2

black EN 1253, EN 13564 100 110 mm without sewage floor slab installation installation-ready Type 5 included



Dimensions Net weight: Gross weight: Cutout dimension, width: Cutout dimension, length: Installation depth: Type of height adjustability: Length: Width: Packaging dimension: Packaging dimension: Packaging dimension:

Tank/drain body Socket version:

Coverage features Type of cover: Cover material: Colour of cover: Load class: Grid size, length: Grid size, width: Grid size, height: Contents of sludge trap:

Cover Grid size, length: Grid size, width: Grid size, height: 3,23 kg 3,55 kg 320 mm 400 mm 216 - 266 mm vertically adjustable upper section 380 mm 300 mm length width height

lateral

Slotted cover Stainless steel 14301 silver K 3 (EN 1253-1) 187 mm 187 mm 4 mm yes

187 mm 187 mm 4 mm