

## Replacement pump KTP/SPZ 1000 230 V, with float switch



### Article information

Item no.: 28301  
 GTIN: 4026092038413  
 Price group: 90

### Description

Variant	
Pump control:	Float switch
General characteristics	
Standard:	EN 12050-1
Type of wastewater:	with sewage
Dimensions	
Net weight:	10,47 kg
Gross weight:	10,8 kg
Packaging dimension:	length
Packaging dimension:	width
Packaging dimension:	height
Pumping device	
Pump:	SPZ 1000
Connection type:	Schuko (earthed contact) 2-pin
Rated current:	5,2 A
Length of mains cable for pump:	5 m
Protection class:	I
Insulation class:	F
Cos phi - power factor:	0,97
Protection class (pump):	IP 68 (3m/48h)
Temperature monitoring:	integrated
Max. temperature (permanent) of conveyed material:	35 °C
Max. pumping height:	10 m
Speed:	2800 U/min
Power P1:	1,2 kW
Power P2:	0,7 kW
Operating mode:	S3 - 50 %
Type of fuse required (electrical protection):	C 16 A

Type of pump connection cable:

H07RN-F 3G 1.5 mm<sup>2</sup>

Control

Mains frequency:

50 Hz

Operating voltage:

230 V

Connection type:

Schuko (earthed contact) 2-pin

Rated current:

5,2 A