

## Replacement pump KTP/SPZ 1000 230 V, cable length 5 m



### Article information

Item no.: 28351  
 GTIN: 4026092038420  
 Price group: 90

### Description

Replacement pump with macerator for wastewater with sewage

#### Variant

Pump control: Control unit

#### General characteristics

Standard: EN 12050-1  
 Type of wastewater: with sewage

#### Dimensions

Net weight: 10,29 kg  
 Gross weight: 10,62 kg  
 Packaging dimension: length  
 Packaging dimension: width  
 Packaging dimension: height

#### Pumping device

Pump: SPZ 1000  
 Connection type: coded plug  
 Operating voltage: 230 V  
 Mains frequency: 50 Hz  
 Protection class: I  
 Insulation class: F  
 Cos phi - power factor: 0,97  
 Protection class (pump): IP 68 (3m/48h)  
 Temperature monitoring: integrated  
 Max. temperature (permanent) of conveyed material: 35 °C  
 Max. pumping height: 10 m  
 Speed: 2800 U/min  
 Power P1: 1,2 kW  
 Power P2: 0,7 kW  
 Operating mode: S3 - 50 %

Type of pump connection cable:	H07RN-F 3G 1.5 mm <sup>2</sup>
Impeller type:	Macerator
Length of mains cable for pump:	5 m
Rated current:	5,2 A
Control	
Operating voltage:	230 V
Connection type:	coded plug
Type of fuse required (electrical protection):	Fuse protection through control unit 230 V