

## Replacement pump KTP/SPZ 1000 230 V, with extended press. pipe connec.



### Article information

Item no.: 28739  
GTIN: 4026092051979  
Price group: 90

### Description

Replacement pump with extended pressure pipe connection and macerator for wastewater with sewage, ready for connection with coded plug

#### General characteristics

Standard:	EN 12050-1
Type of wastewater:	with sewage
ATEX:	no

#### Dimensions

Net weight:	9,67 kg
Gross weight:	10,37 kg
Packaging dimension:	length
Packaging dimension:	width
Packaging dimension:	height

#### Pumping device

Pump:	SPZ 1000
Connection type:	coded plug
Operating voltage:	230 V
Mains frequency:	50 Hz
Rated current:	5,2 A
Protection class:	I
Insulation class:	F
Cos phi - power factor:	0,97
Protection class (pump):	IP 68 (3m/48h)
Temperature monitoring:	integrated
Max. temperature (permanent) of conveyed material:	35 °C
Max. pumping height:	10 m
Speed:	2800 U/min
Power P1:	1,2 kW

Power P2:	0,7 kW
Operating mode:	S3 - 50 %
Type of fuse required (electrical protection):	C 16 A
Type of pump connection cable:	H07RN-F 3G 1.5 mm <sup>2</sup>
Impeller type:	Macerator
Length of mains cable for pump:	5 m
Control	
Connection type:	coded plug
Type of fuse required (electrical protection):	C 16 A