

Replacement pump KTP/SPZ 1000 230 V, with extended press. pipe connec.



Article information

Item no.: 28739
GTIN: 4026092051979
Price group: 90

Description

Replacement pump with extended pressure pipe connection and macerator for wastewater with sewage, ready for connection with coded plug

General characteristics

Standard: EN 12050-1
Type of wastewater: with sewage

Dimensions

Net weight: 9,67 kg
Gross weight: 10,37 kg
Packaging dimension: length
Packaging dimension: width
Packaging dimension: height

Pumping device

Pump: SPZ 1000
Connection type: coded plug
Operating voltage: 230 V
Mains frequency: 50 Hz
Protection class: I
Insulation class: F
Cos phi - power factor: 0,97
Protection class (pump): IP 68 (3m/48h)
Temperature monitoring: integrated
Max. temperature (permanent) of conveyed material: 35 °C
Max. pumping height: 10 m
Speed: 2800 U/min
Power P1: 1,2 kW
Power P2: 0,7 kW
Operating mode: S3 - 50 %

Type of pump connection cable:	H07RN-F 3G 1.5 mm ²
Impeller type:	Macerator
Length of mains cable for pump:	5 m
Rated current:	5,2 A
Control	
Operating voltage:	230 V
Connection type:	coded plug
Type of fuse required (electrical protection):	C 16 A