

Roof drain Press. fl., DN 100, with leaf trap



Article information

Item no.: 45950

GTIN: 4026092001318

Price group: 10

Description

The roof drain for flat roof surfaces is used for point drainage and is equipped with a pressure sealing flange as well as a gravel trap. The recyclable composite material Ecoguss fulfils the highest sound protection requirements, is resistant to aggressive media, can withstand temperatures up to 400 degrees Celsius and has a permanently corrosion-free surface. Note:

Please consult the KESSEL Service Centre for trapezoidal roof areas greater than 2500 sqm.

Variant

System: 100
Heating: without

Waterproofing layer on the drain body: Press sealing flange (suitable for creating

watertight seals)

General characteristics

Nominal size (DN): 100 Outer diameter (OD): 110 mm

Dimensions

Net weight: 0,92 kg Gross weight: 1,11 kg Diameter: 246 mm Cutout dimension, width: 180 mm Cutout dimension, length: 180 mm Length: 246 mm Width: 246 mm Height: 182 mm Packaging dimension: lenath Packaging dimension: width Packaging dimension: height

Tank/drain body



Material of drain body: PP

Coverage features

Type of cover: Leaf trap Cover material: Polymer Colour of cover: black Width of cover: 120 mm Height of cover: 80 mm Length of cover: 120 mm Shape of upper section: round Upper section material: PΡ