

Parking deck drain, Ecoguss Pressure sealing flange, DN 100, square



Article information

Item no.: 48811.01 GTIN: 4026092036099

Price group: 40

Advantages

- Breakproof & load resistant
- withstand temperatures up to 400 degrees
 Celsius

Description

The Ecoguss parking deck drain is used for point drainage and is equipped with a sludge bucket. The recyclable composite material Ecoguss is temperature resistant and has a permanently corrosion-free surface. The outlet socket is suitable for connection to SML cast iron pipes. Separate equipotential bonding is not necessary. For products with pressure sealing flange:

The pressure sealing flange with bolts and screws made of stainless steel is used for the clamping or welding of bitumen and polymer bitumen sheets as well as for polymer and elastomer sealing sheets. Only membranes tested by the manufacturer may be used for watertight seals. The outlet socket is suitable for connection to SML cast iron pipes. With connection option for equipotential bonding. It can be exposed to flames for short periods, 100 up to 400 degrees Celsius.

Variant

System: 125 Contents of sludge trap: yes

Waterproofing layer on the drain body: Press sealing flange (suitable for creating

watertight seals)

4,5

Discharge rate (l/s) with 20 mm backwater:

3 . . . (, .,

General characteristics

Standard: EN 1253-2 Nominal size (DN): 100 Outer diameter (OD): 110 mm

Dimensions

Net weight: 4,88 kg
Gross weight: 5,87 kg
Diameter: 290 mm
Cutout dimension, width: 300 mm
Cutout dimension, length: 300 mm
Length: 290 mm
Width: 290 mm



Packaging dimension: length
Packaging dimension: width
Packaging dimension: height

Tank/drain body

Material of drain body: Ecoguss Socket version: vertical

Coverage features

Type of cover: Round slotted cover

Cover material: Ecoguss Colour of cover: black Width of cover: 234 mm Length of cover: 234 mm Surface: EDM Frame material: **Ecoguss** Locking: Lock & Lift Load class: B 125 (EN 124)

Rim width: 247 mm
Rim length: 247 mm
Shape of upper section: square
Upper section material: Ecoguss
Contents of sludge trap: yes