


Variofix upper section Slotted grating, 304 SST, L 15





Article information

Item no.: 48965

GTIN: 4026092004708

Price group: 70

Advantages

- Different covers selectable
- Including waterproofing membrane

Description

Used in combination with a drain body of the KESSEL modular system, the upper section is suitable for indoor point drainage.

Variant

Seal: Lip seal

Waterproofing layer on the upper section: Enclosed sealing collar to be glued (bd) according to

DIN 18534

Water exposure class in accordance to DIN

18534-1 (up to and including):

W3-I

General characteristics

Sustainable: through the use of recycled material

Dimensions

Vertical adjustment: 23 - 40 mm
Net weight: 2,4 kg
Gross weight: 2,64 kg
Diameter: 312 mm

Type of height adjustability: vertically adjustable upper section

Height: 120 mm
Packaging dimension: length
Packaging dimension: width
Packaging dimension: height

Coverage features



Type of cover: Slotted cover

Cover material: Stainless steel 14301

Colour of cover: silver Surface: pickled

Frame material: Stainless steel 14301

Locking: placed

Load class: L 15 (EN 1253-1)

Grating design: Cross
Rim width: 150 mm
Rim length: 150 mm

Upper section: adjustable in three dimensions

Shape of upper section: square Upper section material: ABS

Mesh size: 23 x 23 mm