



## Drain body Ferrofix Press. fl. Sys 125, DN 100, Vert. out



### Article information

Item no.: 54230  
 GTIN: 4026092053683  
 Price group: 70

### Advantages

- Made of particularly hygienic and mechanically highly resistant stainless steel
- Variably combinable with upper sections

### Description

In combination with a System 125 upper section, the Ferrofix stainless steel drain body is used for point drainage and is equipped with a removable odour trap and a temporary protective cover. The pressure sealing flange with bolts and screws made of stainless steel is used for the clamping or welding of bitumen and polymer bitumen sheets as well as for polymer and elastomer sealing sheets. Only the sealing sheets tested by the manufacturer may be used for watertight seals. The outlet socket is suitable for connection to SML cast iron pipes.

#### Variant

System:	125
Waterproofing layer on the drain body:	Press sealing flange (suitable for creating watertight seals)
Sealing water height:	50 mm

#### General characteristics

Standard:	EN 1253-1
Nominal size (DN):	100
Outer diameter (OD):	110 mm
Approval:	Z-19.53-2414,Z-19.17-1719
Odour trap:	included

#### Dimensions

Net weight:	2,55 kg
Gross weight:	2,84 kg
Length:	273 mm

Width:	273 mm
Height:	201 mm
Packaging dimension:	length
Packaging dimension:	width
Packaging dimension:	height
Tank/drain body	
Number of outlets:	1
Material of drain body:	Stainless steel 14301
Socket version:	vertical