


Ferrofix upper section Gl. flange H:15mm, 300x300mm,insert,M125



Article information

Item no.: 55137
GTIN: 4026092107621
Price group: 70

Advantages

- Made of a particularly hygienic and mechanically highly resistant stainless steel
- Multiple combinations with suitable drain bodies

Description

Used in combination with a drain body of the KESSEL modular system 185, the stainless steel upper section is suitable for indoor point drainage. The upper section is suitable for thin-layered floorings (e.g. epoxy resin) and has a circumferential adhesive joint edge (15 mm deep and 50 mm folded outwards).

Variant

System:	185
Note on installation depth:	For load class M 125, on-site shimming necessary
Waterproofing layer on the upper section:	Adhesive flange (suitable for moisture barriers)

General characteristics

Standard:	EN 1253-1
-----------	-----------

Dimensions

Length:	300 mm
Width:	300 mm
Height:	200 mm

Coverage features

Type of cover:	Ladder grating
Cover material:	Stainless steel 14301
Height of cover:	15 mm
Locking:	unlocked
Load class:	L 15 / M 125 (EN 1253-1)

Grating material:	304 stainless steel
Shape of upper section:	square
Upper section material:	Stainless steel 14301
Cover	
Grating material:	304 stainless steel