


Drain body Ferrofix, one-piece DN 100, hori., 206x206,grated cover L15





Article information

Item no.: 55157

GTIN: 4026092107829

Price group: 70

Advantages

 Made of particularly hygienic and mechanically highly resistant stainless steel

Description

The one-piece Ferrofix System 185 stainless steel floor drain is used for point drainage and is equipped with a removable odour trap, sludge bucket and grated cover. The floor drain is suitable for thin-layered floorings (e.g. epoxy resin) and has an all-round adhesive rim. The outlet socket is suitable for connection to SML cast iron pipes. With a drainage capacity **2.4** l/s with 20 mm build-up.

Variant

System: 185
Contents of sludge trap: yes
Sealing water height: 70 mm
Discharge rate (l/s) with 20 mm threshold: 2,5

Outlet: horizontal

General characteristics

Material: Stainless steel 14301

Outlet: horizontal Odour trap: included

Dimensions

Length:206 mmWidth:206 mmHeight:220 mm

Tank/drain body



Number of outlets: 1

Outlet nominal size (DN): 100 mm

Coverage features

Type of cover: Slotted cover

Cover material:

Load class:

L 15 (EN 1253-1)

Grating material:

304 stainless steel

Shape of upper section: square Contents of sludge trap: yes

Cover

Grating material: 304 stainless steel