


## Ferrofix renovation drain GI fl., DN 50, horizontal, slot grat.



### Article information

Item no.: 59315  
 GTIN: 4026092103029  
 Price group: 70

### Advantages

- Made of particularly hygienic and mechanically highly resistant stainless steel
- ideal for the food industry
- catering kitchens and swimming pools

### Description

The Ferrofix stainless steel renovation drain is equipped with a horizontal outlet DN 50 as well as a removable odour trap.

|  |  |
|--|--|
| Variant                                    |  |
| System:                                    | 125  |
| Waterproofing layer on the upper section:  | Adhesive flange (suitable for moisture barriers) |
| Sealing water height:                      | 50 mm  |
| Discharge rate (l/s) with 20 mm backwater: | 0,8  |

|                         |       |
|-------------------------|-------|
| General characteristics |       |
| Nominal size (DN):      | 50    |
| Outer diameter (OD):    | 50 mm |

|                      |        |
|----------------------|--------|
| Dimensions           |        |
| Net weight:          | 4 kg   |
| Gross weight:        | 4,3 kg |
| Max. design height:  | 107 mm |
| Length:              | 273 mm |
| Width:               | 248 mm |
| Height:              | 107 mm |
| Packaging dimension: | length |
| Packaging dimension: | width  |
| Packaging dimension: | height |

|                         |                       |
|-------------------------|-----------------------|
| Tank/drain body         |                       |
| Number of outlets:      | 1                     |
| Material of drain body: | Stainless steel 14301 |
| Socket version:         | lateral               |

#### Coverage features

|                         |                       |
|-------------------------|-----------------------|
| Type of cover:          | Slotted cover         |
| Cover material:         | Stainless steel 14301 |
| Width of cover:         | 138 mm                |
| Length of cover:        | 138 mm                |
| Locking:                | unlocked              |
| Load class:             | L 15 (EN 1253-1)      |
| Rim width:              | 148 mm                |
| Rim length:             | 148 mm                |
| Upper section material: | Stainless steel 14301 |
| Odour trap:             | included              |