

Yard drain System 200, horiz., slot grat., B 125



Article information

Item no.: 67923B
 GTIN: 4026092038819
 Price group: 10

Advantages

- Recyclable
- Fulfills highest sound protection requirements
- Temperature-resistant up to 400 degrees Celsius

Description

The Ecoguss yard drain is used for point drainage and is equipped with a sludge bucket. The recyclable composite material, Ecoguss fulfils the highest sound protection requirements, can withstand temperatures up to 400 degrees Celsius and has a permanently corrosion-free surface. The outlet socket is suitable for connection to polymer pipes. Separate equipotential bonding is not necessary.

Variant

| | |
|--|-----|
| System: | 200 |
| Contents of sludge trap: | yes |
| Discharge rate (l/s) with 20 mm threshold: | 4,5 |

General characteristics

| | |
|--------------------|-----|
| Nominal size (DN): | 100 |
| Odour trap: | no |

Dimensions

| | |
|----------------------|-------------|
| Vertical adjustment: | 40 - 150 mm |
| Net weight: | 3,96 kg |
| Gross weight: | 4,36 kg |
| Packaging dimension: | length |
| Packaging dimension: | width |
| Packaging dimension: | height |

Tank/drain body

| | |
|-------------------------|---------|
| Number of outlets: | 1 |
| Material of drain body: | Polymer |
| Socket version: | lateral |

Coverage features

| | |
|----------------|---------------------|
| Type of cover: | Round slotted cover |
|----------------|---------------------|

| | |
|--------------------------|----------------|
| Cover material: | Ecoguss |
| Colour of cover: | black |
| Width of cover: | 258 mm |
| Length of cover: | 258 mm |
| Surface: | EDM |
| Frame material: | Ecoguss |
| Locking: | Lock & Lift |
| Load class: | B 125 (EN 124) |
| Rim width: | 258 mm |
| Rim length: | 258 mm |
| Shape of upper section: | square |
| Upper section material: | Ecoguss |
| Contents of sludge trap: | yes |