

## Replacement pump, Pumpfix F DN 100/125, 5 m cable



### Article information

Item no.: 680040  
 GTIN: 4026092062333  
 Price group: 90

### Description

Replacement pump with cover, motor, impeller, blades and pump housing for faecal wastewater

#### Variant

Pump control: Control unit

#### General characteristics

Standard: EN 12050-1  
 Type of wastewater: with sewage

#### Dimensions

Net weight: 13,59 kg  
 Gross weight: 15,14 kg  
 Packaging dimension: length  
 Packaging dimension: width  
 Packaging dimension: height

#### Pumping device

Pump: SPZ 1000  
 Weight, pump: 10 kg  
 Connection type: Schuko (earthed contact) 2-pin  
 Operating voltage: 230 V  
 Mains frequency: 50 Hz  
 Rated current: 5,2 A  
 Protection class: I  
 Insulation class: F  
 Cos phi - power factor: 0,97  
 Protection class (pump): IP 68 (3m/48h)  
 Temperature monitoring: integrated  
 Max. temperature (permanent) of conveyed material: 35 °C  
 Max. pumping height: 10 m  
 Speed: 2800 U/min

Power P1:	1,2 kW
Power P2:	0,7 kW
Operating mode:	S3 - 30 %
Type of fuse required (electrical protection):	C 16 A
Type of pump connection cable:	H07RN-F 3G 1.5 mm <sup>2</sup>
Impeller type:	Macerator
Length of mains cable for pump:	5 m
Control	
Connection type:	Schuko (earthed contact) 2-pin
Type of fuse required (electrical protection):	C 16 A