

## Replacement pump SPF 550 KE 5.5 kW



## **Article information**

Item no.: 680332 GTIN: 4026092067901

Price group: 90

## **Description**

Homogeniser pump for grease separators

Variant

Pump control: Control unit

**Dimensions** 

Net weight: 42,4 kg Gross weight: 42,4 kg Packaging dimension: length Packaging dimension: width Packaging dimension: height

Pumping device

**SPF 550 KF** Pump: Weight, pump: 58 kg

Connection type: Direct connection

400 V Operating voltage: 50 Hz Mains frequency: Rated current: 10,2 A Protection class: I F Insulation class:

Protection class (pump): IP 68 (3m/48h) Temperature monitoring: integrated 35°C

Max. temperature (permanent) of conveyed

material:

Max. pumping height: 19 m

Speed: 2900 U/min Power P1: 5,6 kW Power P2: 4.8 kW Operating mode: S2 - 40 min.

Type of fuse required (electrical protection): Fuse protection through control unit 400 V

Type of pump connection cable: H07RN-F 7G 1.5 mm<sup>2</sup>

Impeller type: Radial impeller with macerating system



Length of mains cable for pump: 5 m

Control

Connection type: Direct connection

Type of fuse required (electrical protection): Fuse protection through control unit 400 V