

Replacement pump TPF 120 400 V, 1.3 kW



Article information

Item no.: 680410
 GTIN: 4026092069653
 Price group: 90

Description

Replacement pump with macerator for faecal wastewater, includes connection adapter for TPF120

Variant

Series: bis 10/2006

General characteristics

Standard: EN 12050-1
 Type of wastewater: with sewage

Dimensions

Net weight: 53,33 kg
 Gross weight: 60 kg
 Packaging dimension: length
 Packaging dimension: width
 Packaging dimension: height

Pumping device

Pump: TPF 120
 Connection type: Direct connection
 Operating voltage: 400 V
 Mains frequency: 50 Hz
 Rated current: 3,56 A
 Protection class: I
 Insulation class: F
 Cos phi - power factor: 0,71
 Protection class (pump): IP 68 (3m/48h)
 Temperature monitoring: controlled via control unit
 Max. temperature (permanent) of conveyed material: 40 °C
 Max. pumping height: 16,6 m
 Speed: 2885 U/min
 Power P1: 1,75 kW

Power P2:	1,3 kW
Operating mode:	S1
Type of fuse required (electrical protection):	Fuse protection through control unit 400 V
Type of pump connection cable:	H07RN-F 7G 1.5 mm ²
Length of mains cable for pump:	10 m
Control	
Connection type:	Direct connection
Type of fuse required (electrical protection):	Fuse protection through control unit 400 V