

## Replacement pump TPF 120 400 V, 1.3 kW



### Article information

Item no.: 680410  
GTIN: 4026092069653  
Price group: 90

### Description

Replacement pump with macerator for faecal wastewater, includes connection adapter for TPF120

#### Variant

Series: bis 10/2006

#### General characteristics

Standard: EN 12050-1  
Type of wastewater: with sewage

#### Dimensions

Net weight: 53,33 kg  
Gross weight: 60 kg  
Packaging dimension: length  
Packaging dimension: width  
Packaging dimension: height

#### Pumping device

Pump: TPF 120  
Connection type: Direct connection  
Rated current: 3,56 A  
Length of mains cable for pump: 10 m  
Protection class: I  
Insulation class: F  
Cos phi - power factor: 0,71  
Protection class (pump): IP 68 (3m/48h)  
Temperature monitoring: controlled via control unit  
Max. temperature (permanent) of conveyed material: 40 °C  
Max. pumping height: 16,6 m  
Speed: 2885 U/min  
Power P1: 1,75 kW  
Power P2: 1,3 kW

Operating mode:	S1
Type of fuse required (electrical protection):	Fuse protection through control unit 400 V
Type of pump connection cable:	H07RN-F 7G 1.5 mm <sup>2</sup>
Control	
Mains frequency:	50 Hz
Operating voltage:	400 V
Connection type:	Direct connection
Rated current:	3,56 A