

Replacement pump pumping station dry installation SPF 4500-S3



Article information

Item no.: 680533
 GTIN: 4026092074947
 Price group: 90

Description

Replacement pump type SPF 4500-S3 for Aqualift F XL pumping station, dry installation

Variant

Pump control: Control unit

General characteristics

Cable length: 10 m

Dimensions

Net weight: 26,5 kg

Gross weight: 29,3 kg

Packaging dimension: length

Packaging dimension: width

Packaging dimension: height

Pumping device

Pump: SPF 4500-S3

Connection type: Direct connection

Operating voltage: 400 V

Mains frequency: 50 Hz

Protection class: I

Insulation class: F

Cos phi - power factor: 0,85

Protection class (pump): IP 68

Temperature monitoring: controlled via control unit

Max. temperature (permanent) of conveyed material: 40 °C

Max. pumping height: 20 m

Speed: 2850 U/min

Power P1: 4,2 kW

Power P2: 3,5 kW

Operating mode: S3 - 50 %

Type of pump connection cable:	H07RN-F 7G 1.5 mm ²
Length of mains cable for pump:	10 m
Rated current:	7,5 A
Control	
Operating voltage:	400 V
Connection type:	Direct connection
Type of fuse required (electrical protection):	Fuse protection through control unit 400 V