

## Replacement pump pumping station dry installation SPF 4500-S3



### Article information

Item no.: 680533  
 GTIN: 4026092074947  
 Price group: 90

### Description

Replacement pump type SPF 4500-S3 for Aqualift F XL pumping station, dry installation

#### Variant

Pump control: Control unit

#### General characteristics

Cable length: 10 m

#### Dimensions

Net weight: 26,5 kg

Gross weight: 29,3 kg

Packaging dimension: length

Packaging dimension: width

Packaging dimension: height

#### Pumping device

Pump: SPF 4500

Connection type: Direct connection

Rated current: 7,5 A

Length of mains cable for pump: 10 m

Protection class: I

Insulation class: F

Cos phi - power factor: 0,85

Protection class (pump): IP 68

Temperature monitoring: controlled via control unit

Max. temperature (permanent) of conveyed material: 40 °C

Max. pumping height: 20 m

Speed: 2850 U/min

Power P1: 4,2 kW

Power P2: 3,5 kW

Operating mode: S3 - 50 %

Type of fuse required (electrical protection):  
Type of pump connection cable:

Fuse protection through control unit 400 V  
H07RN-F 7G 1.5 mm<sup>2</sup>

Control

Mains frequency:

50 Hz

Operating voltage:

400 V

Connection type:

Direct connection

Rated current:

7,5 A