

Replacement pump Aquadive GTF1200 with float switch, 10 m



Article information

Item no.: 680594
 GTIN: 4026092078808
 Price group: 90

Description

Replacement pump, Aquadive GTF 1200 with floater for pumping station

Variant

Pump control: Float switch

General characteristics

Cable length: 10 m
 ATEX: no

Dimensions

Net weight: 11,44 kg
 Gross weight: 11,44 kg
 Packaging dimension: length
 Packaging dimension: width
 Packaging dimension: height

Pumping device

Pump: GTF 1200
 Connection type: Schuko (earthed contact) 2-pin
 Operating voltage: 230 V
 Mains frequency: 50 Hz
 Rated current: 6,2 A
 Protection class: I
 Insulation class: F
 Cos phi - power factor: 0,98
 Protection class (pump): IP 68
 Max. temperature (permanent) of conveyed material: 35 °C
 Max. pumping height: 9 m
 Speed: 2650 U/min
 Power P1: 1,4 kW
 Power P2: 0,84 kW
 Operating mode: S3 - 50 %

Type of fuse required (electrical protection):	C 16 A
Type of pump connection cable:	H07RN-F 3G 1.5 mm ²
Length of mains cable for pump:	10 m
Control	
Connection type:	Schuko (earthed contact) 2-pin
Type of fuse required (electrical protection):	C 16 A