

Replacement pump Aquadive STZ3700 without float switch, 10 m, ATEX



Article information

Item no.: 680606
 GTIN: 4026092078501
 Price group: 90

Description

Replacement pump, Aquadive, STZ 3700, ATEX, without floater, for pumping station, wet installation

Variant

Pump control: Control unit

General characteristics

Cable length: 10 m
 ATEX: yes

Dimensions

Net weight: 43 kg
 Gross weight: 46 kg
 Packaging dimension: length
 Packaging dimension: width
 Packaging dimension: height

Pumping device

Pump: STZ 3700
 Weight, pump: 44 kg
 Connection type: Direct connection
 Operating voltage: 400 V
 Mains frequency: 50 Hz
 Rated current: 6,4 A
 Protection class: I
 Insulation class: H
 Cos phi - power factor: 0,82
 Protection class (pump): IP 68
 Temperature monitoring: controlled via control unit
 Max. temperature (permanent) of conveyed material: 40 °C

| | |
|--|--|
| Max. pumping height: | 35 m |
| Speed: | 2900 U/min |
| Power P1: | 3,7 kW |
| Power P2: | 3,1 kW |
| Operating mode: | S1 |
| Type of fuse required (electrical protection): | Fuse protection through control unit 400 V |
| Type of pump connection cable: | H07RN8-F 6G 1.5 mm ² |
| Impeller type: | Macerator |
| Length of mains cable for pump: | 10 m |
| Control | |
| Connection type: | Direct connection |
| Type of fuse required (electrical protection): | Fuse protection through control unit 400 V |