

Replacement pump STZ 5200 without float switch, ATEX



Article information

Item no.: 680704
GTIN: 4026092081990
Price group: 90

Description

Replacement pump without float switch for pumping station, wet installation

Variant

Pump control: Control unit

General characteristics

Type of wastewater: for wastewater with and without sewage

Dimensions

Net weight: 58 kg
Gross weight: 60 kg
Packaging dimension: length
Packaging dimension: width
Packaging dimension: height

Pumping device

Pump: STZ 5200
Weight, pump: 56 kg
Connection type: Direct connection
Operating voltage: 400 V
Mains frequency: 50 Hz
Rated current: 8,7 A
Protection class: I
Insulation class: H
Cos phi - power factor: 0,89
Protection class (pump): IP 68
Temperature monitoring: integrated
Max. temperature (permanent) of conveyed material: 40 °C
Max. pumping height: 52 m
Speed: 2840 U/min
Power P1: 5,2 kW
Power P2: 4,4 kW

| | |
|--|--|
| Operating mode: | S1 |
| Type of fuse required (electrical protection): | Fuse protection through control unit 400 V |
| Type of pump connection cable: | H07RN8-F PLU 10G 1.5 mm ² |
| Impeller type: | Macerator |
| Length of mains cable for pump: | 10 m |
| Control | |
| Connection type: | Direct connection |
| Type of fuse required (electrical protection): | Fuse protection through control unit 400 V |