

Replacement pump STZ 5200 without float switch, ATEX



Article information

Item no.: 680704
 GTIN: 4026092081990
 Price group: 90

Description

Replacement pump without float switch for pumping station, wet installation

Variant

Pump control: Control unit

General characteristics

Type of wastewater: for wastewater with and without sewage

Dimensions

Net weight: 58 kg
 Gross weight: 60 kg
 Packaging dimension: length
 Packaging dimension: width
 Packaging dimension: height

Pumping device

Pump: STZ 5200
 Weight: 56 kg
 Connection type: Direct connection
 Rated current: 8,7 A
 Length of mains cable for pump: 10 m
 Protection class: I
 Insulation class: H
 Cos phi - power factor: 0,89
 Protection class (pump): IP 68
 Temperature monitoring: integrated
 Max. temperature (permanent) of conveyed material: 40 °C
 Max. pumping height: 52 m
 Speed: 2840 U/min
 Power P1: 5,2 kW
 Power P2: 4,4 kW
 Operating mode: S1

Type of fuse required (electrical protection):
Type of pump connection cable:
Impeller type:

Fuse protection through control unit 400 V
H07RN8-F PLU 10G 1.5 mm²
Macerator

Control

Mains frequency:

50 Hz

Operating voltage:

400 V

Connection type:

Direct connection

Rated current:

8,7 A