

Replacement pump STZ 11000 without float switch, ATEX



Article information

Item no.: 680706
 GTIN: 4026092082010
 Price group: 90

Description

Replacement pump without float switch for pumping station, wet installation

Variant

Pump control:

Control unit

General characteristics

Type of wastewater:

for wastewater with and without sewage

Cable length:

10 m

Dimensions

Net weight:

113 kg

Gross weight:

121 kg

Packaging dimension:

length

Packaging dimension:

width

Packaging dimension:

height

Pumping device

Pump:

STZ 11000

Weight:

107 kg

Connection type:

Direct connection

Rated current:

18,8 A

Length of mains cable for pump:

10 m

Protection class:

I

Insulation class:

H

Cos phi - power factor:

0,89

Protection class (pump):

IP 68

Temperature monitoring:

integrated

Max. temperature (permanent) of conveyed material:

40 °C

Max. pumping height:

68 m

Speed:

2900 U/min

Power P1:

11 kW

Power P2:

9,5 kW

Operating mode:	S1
Type of fuse required (electrical protection):	Fuse protection through control unit 400 V
Type of pump connection cable:	H07RN8-F PLU 10G 1.5 mm ²
Impeller type:	Macerator
Control	
Mains frequency:	50 Hz
Operating voltage:	400 V
Connection type:	Direct connection
Rated current:	18,8 A