

Replacement pump GTK 5200 without float switch



Article information

Item no.: 680708
 GTIN: 4026092082034
 Price group: 90

Description

Replacement pump GTK 5200 without float switch, for pumping station, wet installation

Variant

Pump control: Control unit

General characteristics

Type of wastewater: without sewage

Dimensions

Net weight: 57 kg
 Gross weight: 59 kg
 Packaging dimension: length
 Packaging dimension: width
 Packaging dimension: height

Pumping device

Pump: GTK 5200
 Weight, pump: 56 kg
 Connection type: Direct connection
 Operating voltage: 400 V
 Mains frequency: 50 Hz
 Rated current: 8,7 A
 Protection class: I
 Insulation class: H
 Cos phi - power factor: 0,85
 Protection class (pump): IP 68
 Max. temperature (permanent) of conveyed material: 40 °C
 Max. pumping height: 31,6 m
 Speed: 2840 U/min
 Power P1: 5,2 kW
 Power P2: 4,4 kW

Operating mode:	S3 - 30 %
Type of fuse required (electrical protection):	Fuse protection through control unit 400 V
Type of pump connection cable:	H07RN8-F PLU 10G 1.5 mm ²
Length of mains cable for pump:	10 m
Control	
Connection type:	Direct connection
Type of fuse required (electrical protection):	Fuse protection through control unit 400 V