

Replacement pump KTP 300 res., Minilift L, floor slab installat.



Article information

Item no.: 680955
GTIN: 4026092093825
Price group: 90

Description

Replacement pump resistant to salty media, wastewater from water softening systems and wastewater containing condensate from heating systems.

Dimensions

| | |
|----------------------|---------|
| Net weight: | 4,05 kg |
| Gross weight: | 4,34 kg |
| Packaging dimension: | length |
| Packaging dimension: | width |
| Packaging dimension: | height |

Pumping device

| | |
|--|--------------------------------|
| Pump: | KTP 300 |
| Connection type: | Schuko (earthed contact) 2-pin |
| Operating voltage: | 230 V |
| Mains frequency: | 50 Hz |
| Rated current: | 1,9 A |
| Protection class: | I |
| Protection class (pump): | IP 68 (3m) |
| Max. temperature (permanent) of conveyed material: | 35 °C |
| Max. pumping height: | 6 m |
| Speed: | 2800 U/min |
| Power P1: | 0,34 kW |
| Power P2: | 0,21 kW |
| Operating mode: | S1 |
| Type of fuse required (electrical protection): | C 16 A |
| Type of pump connection cable: | H07RN-F 3G 1.5 mm ² |
| Length of mains cable for pump: | 5 m |

Control

| | |
|--|--------------------------------|
| Operating voltage: | 230 V |
| Connection type: | Schuko (earthed contact) 2-pin |
| Type of fuse required (electrical protection): | C 16 A |