

## Replacement pump GTF 1250 with float switch, 10 m



### Article information

Item no.: 680965  
 GTIN: 4026092095409  
 Price group: 90

### Description

Replacement pump with float switch for wastewater containing faecal matter.

#### Variant

Pump control: Float switch

#### General characteristics

Type of wastewater: without sewage

#### Dimensions

Net weight: 11,1 kg  
 Gross weight: 11,1 kg  
 Packaging dimension: length  
 Packaging dimension: width  
 Packaging dimension: height

#### Pumping device

Pump: GTF 1250  
 Connection type: Schuko (earthed contact) 2-pin  
 Operating voltage: 230 V  
 Protection class (pump): IP 68 (3m)  
 Max. temperature (permanent) of conveyed material: 40 °C  
 Max. pumping height: 11 m  
 Speed: 2700 U/min  
 Power P1: 1,3 kW  
 Power P2: 0,8 kW  
 Operating mode: S3 - 50 %  
 Type of pump connection cable: H07RN-F 3G 1.5 mm<sup>2</sup>  
 Impeller type: Multi-vane impeller  
 Length of mains cable for pump: 10 m  
 Rated current: 5,4 A

#### Control

Operating voltage:	230 V
Connection type:	Schuko (earthed contact) 2-pin
Type of fuse required (electrical protection):	C 16 A