


Backwater valve Staufix DN 90, exposed, Type 1





Article information

Item no.: 720090 GTIN: 4026092076002 Price group: 10

Advantages

- Simple conversion to Staufix Type 2 or StaufixControl
- Flexible installation, various covers available for floor slab installation
- Simple, toolless maintenance and cleaning

Description

The backwater valve for wastewater without sewage is equipped with one mechanical flap which closes automatically in the event of backwater and also serves as an emergency closure to be closed by hand. Thanks to the modular KESSEL system, existing systems can easily be supplemented by a second flap or be converted to the StaufixControl backwater valve.

| Variant Emergency closure: Mechanical backwater flaps: | yes 1 |
|---|---|
| General characteristics Colour: Standard: Nominal size (DN): Outer diameter (OD): Type of wastewater: Installation situation: Delivery state: Backwater protection: | black EN 13564 90 90 mm without sewage exposed drainage pipe installation-ready Type 1 |
| Dimensions Net weight: Gross weight: | 1,3 kg 3,9 kg |



Vertical drop between inlet and outlet: Length: Width: Height: Packaging dimension: Packaging dimension: Packaging dimension:

Coverage features Type of cover: Cover locking: 8 mm 385 mm 167 mm 230 mm length width height

Lockable cover One-handed closure