

## Backwater valve Staufix DN 100, exposed, Type 1



### Article information

Item no.: 720100  
GTIN: 4026092076033  
Price group: 10

### Advantages

- Simple conversion to Staufix Type 2 or StaufixControl
- Flexible installation, various covers available for floor slab installation
- Simple, toolless maintenance and cleaning

### Description

The backwater valve for wastewater without sewage is equipped with one mechanical flap which closes automatically in the event of backwater and also serves as an emergency closure to be closed by hand. Thanks to the modular KESSEL system, existing systems can easily be supplemented by a second flap or be converted to the StaufixControl backwater valve.

#### Variant

|                             |     |
|-----------------------------|-----|
| Emergency closure:          | yes |
| Mechanical backwater flaps: | 1   |

#### General characteristics

|                         |                       |
|-------------------------|-----------------------|
| Colour:                 | black                 |
| Standard:               | EN 13564              |
| Nominal size (DN):      | 100                   |
| Outer diameter (OD):    | 110 mm                |
| Type of wastewater:     | without sewage        |
| Installation situation: | exposed drainage pipe |
| Delivery state:         | installation-ready    |
| Backwater protection:   | Type 1                |

#### Dimensions

|   |         |
|---|---------|
| Net weight:                             | 1,4 kg  |
| Gross weight:                           | 1,79 kg |
| Vertical drop between inlet and outlet: | 8 mm    |
| Length:                                 | 389 mm  |
| Width:                                  | 167 mm  |
| Height:                                 | 230 mm  |
| Packaging dimension:                    | length  |
| Packaging dimension:                    | width   |

Packaging dimension:

height

Coverage features

Type of cover:

Lockable cover

Cover locking:

One-handed closure