

## Backwater valve Staufix Basic DN 125, Type 1, with emergency closure



### Article information

Item no.: 72125  
 GTIN: 4026092002360  
 Price group: 10

### Advantages

- Simple conversion possible using conversion kits
- Optional rat protection flap for additional safety
- Fast and toolless maintenance and cleaning

### Description

The backwater valve for wastewater without sewage is equipped with one mechanical flap which closes automatically in the event of backwater and also serves as an emergency closure to be closed by hand. Thanks to the modular KESSEL system, existing systems can easily be supplemented by a second backwater flap.

#### Variant

|   |     |
|---|-----|
| Stainless steel flap as rat protection: | no  |
| Emergency closure:                      | yes |
| Mechanical backwater flaps:             | 1   |

#### General characteristics

|                         |                       |
|-------------------------|-----------------------|
| Colour:                 | black                 |
| Standard:               | EN 13564              |
| Nominal size (DN):      | 125                   |
| Outer diameter (OD):    | 125 mm                |
| Type of wastewater:     | without sewage        |
| Installation situation: | exposed drainage pipe |
| Delivery state:         | installation-ready    |
| Backwater protection:   | Type 1                |

#### Dimensions

|   |        |
|---|--------|
| Net weight:                             | 2,2 kg |
| Gross weight:                           | 2,2 kg |
| Vertical drop between inlet and outlet: | 9 mm   |
| Length:                                 | 405 mm |
| Width:                                  | 200 mm |
| Height:                                 | 280 mm |
| Packaging dimension:                    | length |

Packaging dimension:  
Packaging dimension:

width  
height

Coverage features  
Cover locking:

Quick-release closure