

Backwater valve Staufix DN 200, exposed, Type 2 R



Article information

Item no.: 730200R GTIN: 4026092076187

Price group: 10

Advantages

- Optional rat protection flap for additional safety
- Flexible installation, various covers available for floor slab installation
- Alternatively available as a module set

Description

The backwater valve for wastewater without sewage is equipped with two mechanical flaps which close automatically in the event of backwater. One flap serves as an emergency closure to be closed by hand. Thanks to the modular KESSEL system, existing systems can easily be converted to the StaufixControl backwater valve.

Variant

Stainless steel flap as rat protection: yes
Emergency closure: yes
Mechanical backwater flaps: 2

General characteristics

Colour: black
Standard: EN 13564
Nominal size (DN): 200
Outer diameter (OD): 200 mm

Note on nominal size: Hydraulics correspond to DN 150

Type of wastewater: without sewage
Installation situation: exposed drainage pipe
Delivery state: installation-ready

Backwater protection: Type 2

Dimensions

Net weight: 3,8 kg
Gross weight: 6,4 kg
Vertical drop between inlet and outlet: 8 mm
Length: 586 mm
Width: 233 mm
Height: 306 mm
Packaging dimension: length



Packaging dimension: width Packaging dimension: height

Coverage features

Type of cover: Lockable cover Cover locking: One-handed closure