


Controlfix clean out DN 150, Floor slab, black





Article information

Item no.: 80150S

GTIN: 4026092004098

Price group: 30

Advantages

- Simple conversion to Staufix SWA
- Fast, simple and toolless maintenance
- Quick and toolless access for cleaning

Description

The Premium clean out for faecal and faecal-free wastewater makes easy access to wastewater pipes possible for inspection and maintenance work. Thanks to the modular KESSEL system, existing systems can easily be converted to a Staufix SWA Premium backwater valve, Staufix FKA or Pumpfix F backwater pumping station.

General characteristics

Colour: black
Nominal size (DN): 150
Outer diameter (OD): 160 mm

Type of wastewater: for wastewater with and without sewage

Installation situation: floor slab installation

Delivery state: Installation-ready (connection parts must be

connected on site)

Dimensions

Net weight: 14 kg
Gross weight: 17,32 kg
Groundwater resistant from lower edge of base 3000 mm

section:

Cutout dimension, width: 750 mm
Cutout dimension, length: 750 mm
Vertical drop between inlet and outlet: 9 mm

Installation depth: 516 - 669 mm

Type of height adjustability: vertically adjustable upper section

Length: 486 mm



Width: 590 mm
Packaging dimension: length
Packaging dimension: width
Packaging dimension: height

Tank/drain body

Socket version: including spigot and socket

Coverage features

Type of cover:

Cover plate
Cover material:

Polymer
Colour of cover:

Width of cover:

Length of cover:

Locking:

Lock & Lift
Load class:

Cover plate

Polymer

black

366 mm

Lock & Lift

Lock & Lift

Lock (EN 1253-1)

Tightness: surface water resistant