

Layer thickness measuring device SonicControl, type OA



Article information

Item no.: 917826
 GTIN: 4026092047316
 Price group: 60

Description

Type OA SonicControl layer thickness measuring device for light liquid separators, with ultrasonic sensor for monitoring and reporting of the oil layer thickness with centimetre accuracy. With mains connection, battery backup and optional connection possibility for a remote signal generator. Incl. fixing set for simple on-site assembly and maintenance.

Cable (for sensor) can be extended on site up to 60 m.

Control unit with optical and acoustic alarm, electronic logbook designed for 12 months, logbook readout option via USB interface.

General characteristics

Approval:	BVS 11 ATEX E 040 X
Cable length:	30 m
ATEX:	yes

Dimensions

Net weight:	6,23 kg
Gross weight:	7,02 kg
Packaging dimension:	length
Packaging dimension:	width
Packaging dimension:	height

Pumping device

Connection type:	Schuko (earthed contact) 2-pin
------------------	--------------------------------

Control

Control unit:	yes
Standby power:	3,4 W
Protection class control unit:	IP 54
Connection type:	Schuko (earthed contact) 2-pin
Length of mains cable for control unit:	1,45 m
Potential-free contact:	yes
GSM interface:	yes
USB interface:	yes

Log book function:	yes
Multi-line display:	yes
Battery buffering:	yes
Self-diagnosis system (SDS):	yes