

## Grease separator EasyClean free NS 3, Direct, Refill in., SonicControl



### Article information

Item no.: 93003.12/D  
GTIN: 4026092063538  
Price group: 60

### Advantages

- Direction of flow can be changed thanks to self-sealing interchangeable hubs (NS 2- NS 10)
- Low-maintenance operation
- Odour-reduced disposal with the tank closed

### Description

The separator for greasy wastewater is suitable for free-standing set-up in frost-protected rooms and comes without metallic components in the tank. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap and has a tapered base for fast and clean disposal. Two odour-tight covers with quick-release closures make easy access possible for cleaning and maintenance work. A direct disposal pipe socket is available for odour-reduced manual disposal. After disposal, a maximum of 3 litres residual sludge volume is left in the tank. 20 year polyethylene warranty.

#### Variant

|                                           |                     |
|-------------------------------------------|---------------------|
| Disposal variant:                         | Direct              |
| Shredder-Mix-System:                      | no                  |
| Sludge bucket:                            | no                  |
| Nominal size (NS):                        | 3                   |
| SonicControl:                             | yes                 |
| Disposal system:                          | Disposal connection |
| Refill inlet in accordance with DIN 1988: | yes                 |
| Type of disposal:                         | manual              |
| Load-bearing capacity (DIN 19901):        | F3                  |

#### General characteristics

|                         |                                                                 |
|-------------------------|-----------------------------------------------------------------|
| Material:               | PE                                                              |
| Standard:               | EN 1825                                                         |
| Installation situation: | free-standing installation                                      |
| Delivery state:         | Installation-ready (connection parts must be connected on site) |
| Scope of delivery:      | Storz-B coupling R 2 1/2" for disposal vehicle connection       |

#### Dimensions

|                                             |                                                                                           |
|---------------------------------------------|-------------------------------------------------------------------------------------------|
| Net weight:                                 | 96,5 kg                                                                                   |
| Gross weight:                               | 126,5 kg                                                                                  |
| Set-up area, length:                        | 1736 mm                                                                                   |
| Set-up area, width:                         | 706 mm                                                                                    |
| Set-up area, height:                        | 1434 mm                                                                                   |
| Required access area, length:               | 1500 mm                                                                                   |
| Required access area, width:                | 680 mm                                                                                    |
| Required access area, height:               | 1434 mm                                                                                   |
| Packaging dimension:                        | length                                                                                    |
| Packaging dimension:                        | width                                                                                     |
| Packaging dimension:                        | height                                                                                    |
| Tank/drain body                             |                                                                                           |
| Nominal pressure (PN):                      | 10                                                                                        |
| Pressure pipe connection (DN):              | 65                                                                                        |
| Pressure pipe connection (OD):              | 75 mm                                                                                     |
| Distance pipe bottom outlet to tank bottom: | 985 mm                                                                                    |
| Distance pipe bottom inlet to tank bottom:  | 1055 mm                                                                                   |
| Outlet nominal size (OD):                   | 110 mm                                                                                    |
| Outlet nominal size (DN):                   | 100 mm                                                                                    |
| Inlet nominal size (OD):                    | 110 mm                                                                                    |
| Inlet nominal size (DN):                    | 100 mm                                                                                    |
| Connection inlet/outlet sockets:            | PE-HD pipes in accordance with DIN 19537, HT pipes in accordance with DIN 19560, PP or AS |
| Servicing opening:                          | 420 mm                                                                                    |
| Coverage features                           |                                                                                           |
| Type of cover:                              | Cover                                                                                     |
| Cover material:                             | Polymer                                                                                   |
| Colour of cover:                            | violet                                                                                    |
| Locking:                                    | Quick-release closure                                                                     |
| Tightness:                                  | odour-tight                                                                               |
| Wastewater contents                         |                                                                                           |
| Separator contents:                         | 300 l                                                                                     |
| Total volume:                               | 600 l                                                                                     |
| Contents of sludge trap:                    | 300 l                                                                                     |
| Storage quantity of grease:                 | 120 l                                                                                     |
| Control                                     |                                                                                           |
| Control unit:                               | no                                                                                        |