

## Grease separator EasyClean free NS 10, Standard, SonicControl



### Article information

Item no.: 93010.02  
GTIN: 4026092061497  
Price group: 60

### Advantages

- Direction of flow can be changed thanks to self-sealing interchangeable hubs (NS 2- NS 10)
- Can be retrofitted up to Auto Mix & Pump
- Low-maintenance operation

### Description

The separator for greasy wastewater is suitable for free-standing set-up in frost-protected rooms and comes without metallic components in the tank. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap and has a tapered base for fast and clean disposal. Two odour-tight covers with quick-release closures make easy access possible for cleaning and maintenance work. Manual disposal is carried out with the tank open. 20 year polyethylene warranty.

#### Variant

|                                           |                          |
|-------------------------------------------|--------------------------|
| Disposal variant:                         | Standard                 |
| Shredder-Mix-System:                      | no                       |
| Sludge bucket:                            | no                       |
| Nominal size (NS):                        | 10                       |
| SonicControl:                             | yes                      |
| Refill inlet in accordance with DIN 1988: | no                       |
| Type of disposal:                         | manual with suction hose |
| Load-bearing capacity (DIN 19901):        | F3                       |

#### General characteristics

|                         |                                                                 |
|-------------------------|-----------------------------------------------------------------|
| Material:               | PE                                                              |
| Installation situation: | free-standing installation                                      |
| Delivery state:         | Installation-ready (connection parts must be connected on site) |

#### Dimensions

|                      |          |
|----------------------|----------|
| Net weight:          | 195,5 kg |
| Gross weight:        | 238,5 kg |
| Set-up area, length: | 2822 mm  |
| Set-up area, width:  | 951 mm   |
| Set-up area, height: | 1653 mm  |

|                               |         |
|-------------------------------|---------|
| Required access area, length: | 2590 mm |
| Required access area, width:  | 951 mm  |
| Required access area, height: | 1653 mm |
| Packaging dimension:          | length  |
| Packaging dimension:          | width   |
| Packaging dimension:          | height  |

#### Tank/drain body

|                                             |                                                                                              |
|---------------------------------------------|----------------------------------------------------------------------------------------------|
| Distance pipe bottom outlet to tank bottom: | 1185 mm                                                                                      |
| Distance pipe bottom inlet to tank bottom:  | 1255 mm                                                                                      |
| Outlet nominal size (OD):                   | 160 mm                                                                                       |
| Outlet nominal size (DN):                   | 150 mm                                                                                       |
| Inlet nominal size (OD):                    | 160 mm                                                                                       |
| Inlet nominal size (DN):                    | 150 mm                                                                                       |
| Connection inlet/outlet sockets:            | PE-HD pipes in accordance with DIN 19537, HT pipes<br>in accordance with DIN 19560, PP or AS |

#### Coverage features

|                  |                       |
|------------------|-----------------------|
| Type of cover:   | Cover                 |
| Cover material:  | Polymer               |
| Colour of cover: | violet                |
| Locking:         | Quick-release closure |
| Tightness:       | odour-tight           |

#### Wastewater contents

|                             |        |
|-----------------------------|--------|
| Separator contents:         | 900 l  |
| Total volume:               | 1900 l |
| Contents of sludge trap:    | 1000 l |
| Storage quantity of grease: | 400 l  |

#### Control

|               |    |
|---------------|----|
| Control unit: | no |
|---------------|----|