

EasySink sediment separator ground, NS 2, Load class A



Article information

Item no.: 97202/00A
 GTIN: 4026092026892
 Price group: 60

Advantages

- Waterproof
- resistant to aggressive wastewater
- Odour-tight tank

Description

The sediment separator is suitable for installation in the ground. The collection tank made of permanently resistant polymer (PE) is equipped with a removable sediment tank (NS 2 with two sediment tanks) made of stainless steel and a hole diameter of 5 mm. An odour trap is installed in the outlet. Access for cleaning and maintenance work is possible via one or several service access covers. 20 year polyethylene warranty. Options:

Variant

Nominal size (NS):
 Type of disposal:

2
 manual with suction hose

General characteristics

Material:
 Installation situation:
 Delivery state:

PE
 underground installation
 Installation-ready (connection parts must be connected on site)

Dimensions

Net weight:
 Gross weight:
 Groundwater resistant from lower edge of base section:
 Installation depth:
 Type of height adjustability:
 Required access area, length:
 Required access area, width:

45 kg
 54 kg
 500 mm
 55 - 405 mm
 vertically adjustable upper section, can be tilted by 5 degrees
 1100 mm
 532 mm

Packaging dimension:	length
Packaging dimension:	width
Packaging dimension:	height
Tank/drain body	
Distance pipe bottom outlet to tank bottom:	380 mm
Distance pipe bottom inlet to tank bottom:	528 mm
Outlet nominal size (OD):	110 mm
Outlet nominal size (DN):	100 mm
Inlet nominal size (OD):	110 mm
Inlet nominal size (DN):	100 mm
Connection inlet/outlet sockets:	PE-HD pipes in accordance with DIN 19537, PVC-KG pipes in accordance with DIN 19534, PP or AS
Clear width of entry (LW):	400 mm
Volume of collecting tank:	32 l
Coverage features	
Type of cover:	Cover plate
Cover material:	Polymer
Colour of cover:	black
Width of cover:	364 mm
Height of cover:	46 mm
Length of cover:	364 mm
Locking:	locked
Load class:	A 15 (EN 124)
Tightness:	odour-tight and surface water resistant
Odour trap:	included
Control	
Control unit:	no