

EasySink sediment separator ground, NS 2, Class D



Article information

Item no.: 97202/00D GTIN: 4026092026915 Price group: 60

Advantages

- Waterproof
- resistant to aggressive wastewater
- Odour-tight tank

Description

The sediment separator is suitable for installation in the ground. The collection tank made of permanently resistant polymer (PE) is equipped with a removable sediment tank (NS 2 with two sediment tanks) made of stainless steel and a hole diameter of 5 mm. An odour trap is installed in the outlet. Access for cleaning and maintenance work is possible via one or several service access covers. 20 year polyethylene warranty. Options:

Variant Nominal size (NS): Type of disposal: Load-bearing capacity (DIN 19901):

General characteristics Material: Installation situation: Delivery state:

Odour trap:

Dimensions Net weight: Gross weight: Groundwater resistant from lower edge of base section: Installation depth: Type of height adjustability: Hole diameter of sediment tank

2,00 manual with suction hose E4

ΡE

underground installation Installation-ready (connection parts must be connected on site) included

91 kg 100 kg 500 mm

55 - 405 mm vertically adjustable upper section, can be tilted by 5 degrees



Required access area, length: Required access area, width: Packaging dimension: Packaging dimension: Packaging dimension:	1100 mm 532 mm length width height
Tank/drain body	
Distance pipe bottom outlet to tank bottom:	380 mm
Distance pipe bottom inlet to tank bottom:	528 mm
Outlet nominal size (OD):	110 mm
Outlet nominal size (DN):	100 mm
Inlet nominal size (OD):	110 mm
Inlet nominal size (DN):	100 mm
Connection inlet/outlet sockets:	PE-HD pipes in accordance with DIN 19537, PVC-KG
	pipes in accordance with DIN 19534, PP or AS
Clear width of entry (LW):	400 mm
Volume of collecting tank:	32 l
Coverage features	
Type of cover:	Cover plate
Cover material:	Grey iron
Colour of cover:	black
Width of cover:	395 mm
Height of cover:	52 mm
Length of cover:	395 mm
Locking:	locked
Load class:	D 400 (EN 124)
Tightness:	odour-tight and surface water resistant

Control Control unit:

no