

## Grease separator EasyClean free SkimTech Premium, NS 2

### Article information

Item no.: 99002.01P

GTIN:

Price group: 60

### Description

#### Variant

Shredder-Mix-System: no

Nominal size (NS): 2

Sampling device: yes

#### General characteristics

Material: PE-HD

Standard: EN 1825

Installation situation: free-standing installation

Delivery state: Pre-mounted for final assembly on site (pumps and sensor system must be fitted on site and control unit must be connected)

#### Dimensions

Net weight: 320 kg

Gross weight: 440 kg

Operating weight: 1790 kg + 2 \* 60 kg (Fässer)

Empty weight: 320 kg

Set-up area, length: 3850 mm

Set-up area, width: 1450 mm

Set-up area, height: 2420 mm

Required access area, length: 2300 mm

Required access area, width: 960 mm

Required access area, height: 1950 mm

Packaging dimension: length

Packaging dimension: width

Packaging dimension: height

#### Tank/drain body

Distance from centre of outlet pipe to tank bottom: 1200 mm

Distance pipe bottom outlet to tank bottom: 1200 mm

Distance pipe bottom inlet to tank bottom: 1545 mm

Outlet nominal size (DN): 100 mm

Inlet nominal size (DN): 100 mm

#### Wastewater contents

|                                |                   |
|--------------------------------|-------------------|
| Separator contents:            | 1470 l            |
| Working temperature:           | 0 - 40 °C         |
| Total volume:                  | 1470 l            |
| Pumping device                 |                   |
| Connection type:               | Direct connection |
| Rated current:                 | 0,4 - 0,63 A      |
| Control                        |                   |
| Control unit:                  | yes               |
| Motor protection switch:       | yes               |
| Standby power:                 | 5 W               |
| Type of fuse required (RCD):   | 30 mA             |
| Protection class control unit: | IP 54             |
| Mains frequency:               | 50 Hz             |
| Operating voltage:             | 400 V             |
| Connection type:               | Direct connection |
| Potential-free contact:        | yes               |
| GSM interface:                 | yes               |
| USB interface:                 | yes               |
| Log book function:             | yes               |
| Multi-line display:            | yes               |
| Battery buffering:             | no                |
| Self-diagnosis system (SDS):   | yes               |
| Max. input power:              | 0,44 kW           |
| Working temperature:           | 0 - 40 °C         |
| Rated current:                 | 0,4 - 0,63 A      |